

Workforce management, intelligently

A member of the **Global** series



Prodigy™ — The ideal blend of performance, function, style, and affordability designed for essential workforce management functionality.

Prodigy is for those who demand a rich suite of features at an affordable price: plug and play, Web services, customizable function keys, optional biometrics, smartcards, and more!

Biometric options protect employees' personal information and eliminate costly buddy-punching.

Prodigy features include:

- Internet appliance
- Plug and play
- On-board and remote diagnostics
- Biometric options for increased personal security
- Programmable function keys
- Ergonomic design with angled card slot
- Works in WAN and LAN environments, including GSM/GPRS modem and Ethernet
- Optional power-over-Ethernet module

Answers for HR Professionals™



To learn more about ATS and Prodigy, visit www.accu-time.com or call 860-870-5000.



Specifications

| | |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DISPLAY | 128 x 32 pixel LCD |
| CLOCK | Battery-backed real-time clock, 12- or 24-hour format, USA or international (quartz precision) |
| KEYPAD | 16-key tactile 4x4 matrix Numeric keypad, 0-9 Two software-defined function keys In/Out and Clear/Enter keys Customizable overlay allows for unique graphic options |
| MEMORY | Linux: 16 MB RAM and 32 MB flash Optional Java: 128 MB RAM and 128 MB flash |
| PROGRAMMING | Java™ option Web services capable ATS Universal Command Set or third-party custom application packages |
| PLATFORM | Linux® |
| DIAGNOSTICS | On-board diagnostics, and remote diagnostic capability |
| INTERFACE | Standard 802.3 10/100BASE-T Ethernet with DHCP Optional EIA standard RS232 Optional internal modem (FCC Part 68 certified) Optional GSM/GPRS modem USB port for mass storage device |
| ENCLOSURE | Advanced composite enclosure |
| POWER | 12 VDC (nominal) 1.25A, 15W maximum Optional uninterruptible power supply with charger Optional IEEE 802.3af-compliant power over Ethernet |
| ENVIRONMENT | Operating temperature: 0° to 50°C (32° to +122°F) Storage temperature: -20° to 80°C (-4° to +176°F) |
| PHYSICAL | 7.25" x 8.40" x 3.95" (18.4cm x 21.3cm x 10cm) |
| CERTIFICATIONS | CE Mark, FCC Part 15 Class A |
| ACCESSORIES | <ul style="list-style-type: none"> • Biometric readers – 1:1 and 1:n – fingerscan • Integrated visible or infrared bar code readers • Integrated magnetic readers • Smartcard readers – contactless (Mifare™ and iClass®) • Integrated proximity readers • Solid-state or dry-contact relay modules • Serial interface for printer |

Accu-Time Systems, Inc.

One Accu-Time Plaza
Route 83
Ellington, CT 06029

1-800-355-4648

sales@accu-time.com

www.accu-time.com

TEL: (860) 870-5000

FAX: (860) 872-1511

EMAIL: sales@accu-time.com

Accu-Tech Systems Ltd

C1 Caerphilly Business Park
Caerphilly
Mid Glamorgan
CF83 3ED
United Kingdom

EMEA

+44 (0) 2920 885599

enquire@accu-tech.co.uk

www.accu-tech.co.uk

Continental Europe

+31 (0) 318 75 41 33

Latin America

ventas@accu-time.com

Connecticut • Chicago • Sarasota • Boston • United Kingdom • Netherlands



**All of the ATS
Global Series
products are
100% RoHS
compliant**